

**Silex® Spectrum Burnishing Pads** are excellent pads designed for durability and longevity for a wide variety of applications; burnishing, polishing and maintenance.

**Silex® Spectrum Burnishing Pads** are diamond impregnated throughout the entire pad creating a stronger, wear and tear resistant pad at an economical price. The diamond powders inside the pads provide extended life due to the ability to use either side creating a stronger, more durable tool for most flooring situations.

### PRODUCT USAGE

**Silex® Spectrum Burnishing Pads** are primarily used as a burnishing pad for high speed burnishing machines to create the heat needed in the application of most guards or sealers specified in concrete polishing. The versatility of diamond powders inside the pad also make it the ideal tool for honing and polishing the guards or sealers to get the highest *D.O.I. and Gloss* points available on film forming protections.

The **Silex® Spectrum Burnishing Pads** are also ideal for cleaning &/or maintaining floors of most types including terrazzo, overlays, VCT, counter tops, natural stone and concrete. When used in a regular maintenance program the **Silex® Spectrum Burnishing Pads** are extraordinary. These pads may be used wet or dry and are available in various sizes to meet most maintenance machines dimensions including swing type and automatic floor scrubbing machines.

### BENEFITS

- Burnishing
- Cleaning
- Refurbishing
- Can be Used Wet or Dry
- Maintaining Concrete, Terrazzo & Natural Stone Floors of All Types.
- The 5" is used by Fabricators to clean, buff and finish many varieties of counter top surfaces.

### SPECIFICATIONS

Color Coded	Grit	Thickness	Diameter	Max Speed	Usage
<b>Yellow</b>	200 Grit	1 inch	3" 5" 7" 9" 11" 13" 17" 20" 25" 27"	3000 RPM	Wet or Dry
<b>Silver</b>	400 Grit	1 inch	5" 7" 9" 11" 13" 17" 20" 25" 27"	3000 RPM	Wet or Dry
<b>Green</b>	800 Grit	1 inch	3" 5" 7" 9" 11" 13" 17" 20" 25" 27"	3000 RPM	Wet or Dry
<b>Red</b>	1500 Grit	1 inch	5" 7" 9" 11" 13" 17" 20" 25" 27"	3000 RPM	Wet or Dry
<b>Black</b>	3000 Grit	1 inch	3" 5" 7" 9" 11" 13" 17" 20" 25" 27"	3000 RPM	Wet or Dry

Coverage can vary from surface to surface depending on roughness, porosity and density of the medium being applied. Application technique can also vary the coverage. On flat, dense surfaces the coverage should generally range from 10,000 to 20,000 square feet per pad.



1.866.295.5512 | 5220 Gaines Street San Diego, CA 92110  
 info@silexsystem.com | www.silexsystem.com



Safety Precautions: Proper safety procedures should be followed at all times while handling these products. Refer to the Safety Data Sheets (SDS) for important health/safety information before use. Safety Data Sheets are provided on our website in a downloadable .pdf under each product or contact our office at 1-844-239-4056.